

*** Patented MAX In-Wall™
Technical Specifications**

MAX In-Wall™ S-VIDEO Module



The **MAX In-Wall™ SVIDEO Module** inserts into any **MIW-POWER** unit to protect against surges on both signal and power lines; thus, eliminating potential grounding problems by creating an Isolated Ground Reference for the remote equipment. The **MIW-SVIDEO** accepts component video and S-Video signal lines running between source components and remote equipment. Devices connect to standard RCA and S-Video jacks on the face of the module. RCA jacks may also be used with composite video and L/R audio. Protect multiple signal lines with one module and the installation flexibility the **MIW-SVIDEO** delivers.

GENERAL

Product Name	MAX In-Wall™ S-Video Module
Part Number	MIW-SVideo
Retail Price	\$59.95
Application	Custom Home Theater Systems
Power CordNO
UL® / cUL Listed (1449 2nd Edition)YES

SIGNAL LINE PROTECTION

Attenuation	<.06dB, 0-38MHz, <.19dB at 100MHz
Wires Protected	S-Video: 2RG179/U Cables (4 Wires), RCA: 3 RG179 U Cables (6 Wires)
Protection Mode	Signal Sheath to Ground
Clamping9.0V

PRODUCT WARRANTY

Product Warranty3 years
------------------------	----------

ORDERING INFORMATION

Unit Dimensions1.19"W x 5.50"L x 2.88"H
Individual Unit UPC0 50616 00740 5
Packaging TypeRetail Box
Packaging Dimensions2.95"W x 1.35"L x 7.85"H
Unit Weight (packaged)0.6 lbs.
Units per Inner Pack6
Inner Pack UPC3 00 50616 00740 6
Inner Pack Dimensions6.50"W x 4.80"L x 8.40"H
Inner Pack Weigh4.0 lbs.
Units per Master Carton24 (4 Inner Packs)
Master Carton UPC5 00 50616 00740 0
Master Carton Dimensions9.90"W x 13.30"D x 8.70"H
Master Carton Weight17 lbs.